

Learning Glass iC-LGE30 product overview & specifications

Model Part Number:	iC-LGE30
Model Title:	Learning Glass Europe, 30" Mobile Lightboard with Integrated Camera
Model description:	Learning Glass Europe 30-inch Mobile Lightboard, with integrated 4K camera, power supply, dimmers, adjustable legs
Features:	<p>Laser tested, low-iron tempered glass. Surface treated for improved scratch resistance and easier cleaning</p> <p>4K Camera with 4K@30/25 CMOS 1/2.7" image sensor</p> <p>Presenter lighting element built into frame (no need for external lights)</p> <p>Internal LED's designed for optimal illumination</p> <p>Internal LED's AND presenter lights have adjustable brightness control for different filming environments</p> <p>Designed to be easily transportable</p> <p>Working surface area: 66cm x 37cm</p> <p>Adjustable height: Min 60cm, Max 67cm</p>
Installation time:	15 minutes



1. Introduction

We launched the iC-Learning Glass to enhance the user experience, with the goal to make using our lightboard easier than ever. Our purpose built, integrated, 4K camera (with 4K@30/25 CMOS 1/2.7" image sensor), works seamlessly with the Learning Glass lightboard, making it easy to create powerful, engaging, lightboard content at the touch of a button. The iC-LGE30 Lightboard features our surface treated, smudge-free, safety glass, ensuring best clarity and optical performance. The working surface area is 66cm x 37cm, and at under 6kg, the unit is easily transportable.

Whether you are a teacher, trainer or business professional, this product can be used at home or in the office with minimal set-up time. At a width of 73.5cm it will rest comfortably on the average desk or table, and with a weight of 6kg is easily transportable. This Lightboard is ideal for users that are looking for a hassle free, 'plug and play' solution as there is no need to set-up and configure your own camera.

The Learning Glass uses best in-class components. Our LED's are a high quality, high density, silicone encased (waterproof) design. They have been tested with over a 100,000-hour lifespan with little to no degradation in performance. All of our Lightboard products have fitted external presenter lighting elements, designed to eliminate the need for any additional lighting whilst filming. This is extremely critical in avoiding light spillage and unwanted reflections. They produce a natural white light operating at 4000K. Both internal and external LED's have dimmer control units using pulse width modulation (PWM) to control brightness. These control units operate at extremely high frequency (12kHz) to avoid any 'flicker effect' that may occur with cameras operating at different frame rates and shutter speeds.

Assembly time is around 15 minutes and requires one person.


2. Lightboard Specifications

ELECTRICAL	
Colour Temperature	4000K
CRI Rating	90+
Max Brightness	<4
Viewing Angle	180°
Input Voltage Range	240V
Input Voltage Frequency	50-60Hz
Max Continuous Power	40W
MECHANICAL	
Dimensions with max height	73.5cm x 44.2cm x 3cm
Work Space - Glass surface (cm)	66cm / 37cm
Height Min/Max with legs	60cm / 67cm
Frame Material	High Strength Aluminium
Glass Material	Diamond™ Tempered Glass
Weight (with/without camera attached)	6kg/5kg
Connectors	DC 2.1mm Barrel Jack
ENVIRONMENTAL	
Operation Temperature	-40°C to 85°C
Storage Temperature	-40°C to 105°C
Relative Humidity	40% to 95% Electrical

3. Camera Specifications

Image Sensor	4K@30/25 CMOS 1/2.7"
Max. Resolution	3840(H) *2160 (V)
Video Formats with laptop	4K@30/25 1080p60/50/30/25
(Video Formats with XT)	1080p30 / 720p30
Compression format	Compressed (H.264) on USB or uncompressed on HDMI
Focal Length	f=2.8mm
Min object distance (wide)	500mm
Minimum illumination	0.5 Lux @ (F1.8, AGC ON)
HFoV	104° (up to 123°)
VFoV	68° (up to 80°)
Digital Zoom	8X
Pan and Tilt Range	ePTZ
Connecting Port type	USB 3.0 & HDMI
Serial Control	Via USB
Auto Focus	Support
Camera mount	Tripod screw hole (1/4-20 UNC)
Video configurations	White balance (auto/manual); Focus Mode (auto/manual); Sharpness; Backlight; Exposure Compensation; Picture (auto/manual) and WDR level
Weight	0.34Kg
Voltage Range	DC5V(USB)
Current consumption (max)	600mA
Microphone	frequency response 50Hz – 8KHz, 3m radius omni (6m diameter), coverage 360°
Far end camera control	Through XT codec (H.224, H.281)
Dimensions (w/h/d)	194mm x 34mm x 42mm (without bracket)
Operating System support	Windows, MAC-OS X

4. Lightboard Specifications



Dimensions in centimetres

5. Camera Dimensions



6. Wiring Block Diagram

Learning Glass LightGlass Wiring Diagram

